

Case:

Unit is constructed using fully doweled 0.75" double-sided thermal fused laminate (TFL) with 0.75" sub-top/sub-bottom, 1" matching top, casebody has matching 3mm PVC edge banding. Each unit has 3" heavy duty casters for mobility (2 locking, 2 non-locking, casters require field assembly)

Drawers:

Fully doweled 0.75" matching TFL box w/5mm PVC edge banding, 0.75" TFL front w/3mm PVC edge banding, wire pulls, standard heavy duty side mount steel ball bearing glide.

Doors:

0.75" TFL, 3mm PVC edge banding, wire pulls, heavy duty 5-knuckle hinge with 270° swing allows doors to lay flat.

Shelves:

Double sided TFL shelves (fixes are fully doweled, adjustable have 4 double-pin shelf clips)

Base:

Integrated, fully finished base with built in levelers adjustable from inside cabinet.

Shipping Class: Density Based Class
NMFC#: 80440


Features:




Shelves and double-pin clips




Heavy-duty casters



Built-in levelers



Heavy duty drawer glides



Wire pulls



SS1000-AC



SS6040-AC

Adjustable Shelf Flat Storage

<i>Model #</i>	<i>Description</i>	<i>WxHxD</i>	<i>Weight</i>
SS1000-AC	Flat Storage, 4 Adjustable Shelves, w/o Doors, Casters	48" x 36" x 30"	285

4 Drawer Flat Storage

<i>Model #</i>	<i>Description</i>	<i>WxHxD</i>	<i>Weight</i>
SS6040-AC	Flat Storage, 5 Drawers, Casters	48" x 36" x 30"	410

4 Roll-Out Flat Storage

<i>Model #</i>	<i>Description</i>	<i>WxHxD</i>	<i>Weight</i>
SS1604-AC	Flat Storage, 4 Roll-out Shelves, w/o Doors, Casters	48" x 36" x 30"	325
SS1605-AC	Flat Storage, 4 Roll-out Shelves, w/Doors, Casters	48" x 36" x 30"	370