

iXchange Wall specifications

Construction:

Unit is constructed using .75" thick particle board with thermal fused laminate on both sides with TFL top over subtop. Doors, drawers and top edges are finished using 3mm PVC edge banding. Double-sided adjustable shelves have four double pin shelf clips per shelf to prevent the shelves from sliding out or tipping. Each unit has built-in corner levelers which are accessible from the inside for easy leveling of the unit. 6-point adjustable concealed European hinge with 120 degree opening. 4" Wire pull style handles and integrated design locks. Drawers are fully doweled, 0.5" white TFL box w/3mm PVC edge banding, 0.75" matching TFL front w/3mm PVC edge banding, wire pulls and standard full extension side mount steel ball bearing glides.

Whiteboards:

Aluminum horizontal sliding panel system with two whiteboards standard, optional third whiteboard. Porcelain-on-steel marker surface guarantees a durable, high-performance board. Marker board frame constructed of anodized aluminum trim and includes a cork map rail. Magnetic panels glide on nylon rollers for smooth operation. Finger pull for easy operation and tray for markers.

Assembly:

Each unit is factory assembled using dowel construction. Field assembly of entire unit to include installation of the board and rail system.

Shipping Class:

Density Based Class



SSW0802

iXchange Learning Wall Model Numbers:

| Model # | W" x D" x H" | Weight | |
|---------|------------------|---------|--|
| SSW0801 | 96" x 24" x 84" | 1110 | |
| SSW0802 | 96" x 24" x 84" | 1085 | |
| SSW1001 | 120″ x 24″ x 84″ | 1270 | |
| SSW1002 | 120" x 24" x 84" | 1360 | |
| SSW1201 | 144" x 24" x 84" | 1550 | |
| SSW1202 | 144" x 24" x 84" | 1575 | |
| SSW1203 | 144" x 24" x 84" | 1585 | |
| | | | |
| | | | |
| SSW0801 | SSW0802 | SSW1001 | |





SSW1002

SSW1202



SSW1201

SSW1203





4" Wire Pulls