

### Construction:

Unit is constructed using .75" thick particle board with thermofused laminate or high pressure laminate on both sides. Upper and lower fixed shelves are optional. Edges are finished using 3mm PVC. Opening size will vary depending on the amount of dividers and width of the unit. One single or double prong coat hook will be provided below each compartment. Coat hooks are mounted with a steel threaded insert to prevent hooks from pulling out. If units are wall hung we recommend using the steel base structure. Steel base structure consists of 16-gauge steel wall mount angle brackets and 16-gauge sheet steel powder coated black.

Units can be fitted with optional steel rod shelf.

### Assembly:

Each unit is factory assembled using dowel construction. Steel base structure is field installed. Cubbies and base structures are sold separately.

### Shipping Class:

125

### Tall Cubbies:

Model#	Description	W"	H"	D"
TCB01	Open	24", 36", or 48"	48", 60", or 72"	14"
TCB02	Open, Fixed Top Shelf	24", 36", or 48"	48", 60", or 72"	14"
TCB03	Open, Fixed Bottom Shelf	24", 36", or 48"	48", 60", or 72"	14"
TCB04	Open, Fixed Top and Bottom Shelf	24", 36", or 48"	48", 60", or 72"	14"

### Compartment Chart:


W"	Compartments
24"	2
36"	3
48"	4



Double Prong Garment Hook



Single Prong Garment Hook



Optional Steel Rod Shelf



Specs subject to change. V121517