



Specifications:

Thickness - 0.75", 1.25", 1.625", or 1.75" available
Finishes - Standard or custom laminates
Sizes -Up to 60"D x 144"L
Core Material - Partical board core with HPL on top, black phenolic backer
Edge Profiles - .5 PVC square edge on all four sides
Backer - Phenolic backer
Options - Bullnose edge -BN

Field Installation:

Drilling - Fasteners with a deep thread are recommended. Pre-drilling the holes are recommended. Take into consideration the thickness of the top when selecting screw length for the edge, bottom or top surface.

Cutting - A sharp, carbide cross-cut blade is recommended. Cut the top bottom side up to prevent chipping. In instances where the top can only be cut top side up tape the edge that will be cut and make the cut line through the center of the tape.

Care & Maintenance:

The laminate surface may be cleaned with warm water and mild soaps, such as those used for hands or dishes. Heavy solvents can effect edging adhesion.

Laminate Top Overview:

Laminate edge - A hand-applied, precision plastic laminate edge. Square corners.



Shipping Details

Class: 70 NMFC#: 83620-2 Ground: Yes, with limitations Package: Carton

*All tops over 60"L must have extra support in addition to the legs by adding additional legs and/or support bar to prevent bowing.

Optional Features:



Grommet (-GR)



Markerboard top (-__MB)



4" square self-edge backsplash 4" square PVC edge backsplash



Sink cutout



Angle cut